


EMBOUTS ORFS DSP - DOUBLE 6 PANS

EMBOUT FEMELLE DROIT



DONNÉES TECHNIQUES

Joint facial



Référence	Désignation	S (int. tuyaux)			F	
		module	inch	mm	inch	mm
SFORFDSP00404	S 06 FORFS 9/16 DSP	4	1/4"	6,35	9/16	12,75
SFORFDSP00406	S 06 FORFS 11/16 DSP	4	1/4"	6,35	11/16	15,73
SFORFDSP00506	S 08 FORFS 11/16 DSP	5	5/16"	8	11/16	15,73
SFORFDSP00606	S 10 FORFS 11/16 DSP	6	3/8"	9,5	11/16	15,73
SFORFDSP00608	S 10 FORFS 13/16 DSP	6	3/8"	9,5	13/16	18,9
SFORFDSP00806	S 13 FORFS 11/16 DSP	8	1/2"	12,7	11/16	15,73
SFORFDSP00808	S 13 FORFS 13/16 DSP	8	1/2"	12,7	13/16	18,9
SFORFDSP00810	S 13 FORFS 1" DSP	8	1/2"	12,7	1"	23,45
SFORFDSP00812	S 13 FORFS 1*3/16 DSP	8	1/2"	12,7	1*3/16	27,87
SFORFDSP01008	S 16 FORFS 13/16 DSP	10	5/8"	15,9	13/16	18,9
SFORFDSP01010	S 16 FORFS 1" DSP	10	5/8"	15,9	1"	23,45
SFORFDSP01012	S 16 FORFS 1*3/16 DSP	10	5/8"	15,9	1*3/16	27,87
SFORFDSP01210	S 19 FORFS 1" DSP	12	3/4"	19	1"	23,45
SFORFDSP01212	S 19 FORFS 1*3/16 DSP	12	3/4"	19	1*3/16	27,87
SFORFDSP01216	S 19 FORFS 1*7/16 DSP	12	3/4"	19	1*7/16	34,22
SFORFDSP01616	S 25 FORFS 1*7/16 DSP	16	1"	25,4	1*7/16	34,22
SFORFDSP01620	S 25 FORFS 1*11/16 DSP	16	1"	25,4	1*11/16	40,57
SFORFDSP02020	S 32 FORFS 1*11/16 DSP	20	1*1/4	31,8	1*11/16	40,57
SFORFDSP02424	S 38 FORFS 2" DSP	24	1*1/2	38,1	2"	48,51

www.isoflex.fr

Tel : +33(0)2 41 39 98 98 - contact@isoflex.fr

ANGERS (49) - LOUDEAC (22) - NANTES (44) - CAEN (14) - AVIGNON (84) - ORLÉANS (45)