

EMBOUTS INTERLOCK

JIC

EMBOUT MÂLE DROIT



DONNÉES TECHNIQUES

Filetage UNF - cône 74°



Référence	Désignation	S (int. tuyaux)			Dimensions			
		module	inch	mm	filetage	F/p	pas	D.I
IMJI001012	IN 16 MJI 1"1/16	10	5/8"	15,9	1"1/16	12	2,116	26,98
IMJI001212	IN 19 MJI 1"1/16	12	3/4"	19	1"1/16	12	2,116	26,98
IMJI001214	IN 19 MJI 1"3/16	12	3/4"	19	1"3/16	12	2,116	30,16
IMJI001216	IN 19 MJI 1"5/16	12	3/4"	19	1"5/16	12	2,116	33,33
IMJI001616	IN 25 MJI 1"5/16	16	1"	25,4	1"5/16	12	2,116	33,33
IMJI001620	IN 25 MJI 1"5/8	16	1"	25,4	1"5/8	12	2,116	41,27
IMJI002020	IN 32 MJI 1"5/8	20	1"1/4	31,8	1"5/8	12	2,116	41,27
IMJI002024	IN 32 MJI 1"7/8	20	1"1/4	31,8	1"7/8	12	2,116	47,62
IMJI002424	IN 38 MJI 1"7/8	24	1"1/2	38,1	1"7/8	12	2,116	47,62
IMJI003232	IN 50 MJI 2"1/2	32	2"	50,8	2"1/2	12	2,116	63,5

PRODUITS SIMILAIRES

Cet embout existe également en femelle droit ou coudé 45°, 90° et 90° courbe haute.